ITALY ATS AIRSPACE CLASSIFICATIONS

	Α	B (1)	С	D	E	
	SEPARATION All aircraft	SEPARATION All aircraft	SEPARATION IFR from IFR IFR from VFR	SEPARATION IFR from IFR	SEPARATION IFR from IFR	SEPARATIO
l F	SERVICES Air traffic control service VMC MINIMA (4)	SERVICES Air traffic control service	SERVICES Air traffic control service	SERVICES Air traffic control service including traffic information about VFR flights (and traffic avoidance advise on request)	SERVICES Air traffic control service and Flight information service about VFR flights	SERVICES
	8 km FL 100 5 km 1000 ft 1500 m 1500 m 1000 ft 5 km	VMC MINIMA As for Class (4) A airspace	VMC MINIMA As for Class (4) A airspace	VMC MINIMA As for Class (4) A airspace	VMC MINIMA As for Class (4) A airspace	VMC MINIM (4)
R	SPEED Not applicable	SPEED Not applicable	SPEED Not applicable	SPEED LIMITATION (2)	SPEED LIMITATION (2) below FL 100	SPEED LIMITATION (2)
	RADIO	RADIO	RADIO	RADIO	RADIO	RADIO
	TRANSPONDER A,C	TRANSPONDER A,C	TRANSPONDER A,C	TRANSPONDER A,C	TRANSPONDER A,C	TRANSPON
	CLEARANCE	CLEARANCE	CLEARANCE	CLEARANCE EATC	CLEARANCE EATOF	CLEARANC
		SEPARATION All aircraft	SEPARATION VFR from IFR	SEPARATION Not provided	SEPARATION Not provided	SEPARATION
V F R		SERVICES Air traffic control service	SERVICES Air traffic control service for separation from IFR VFR traffic information (and traffic avoidance advice on request)	SERVICES Traffic information in respect of all other flights (traffic avoidance advice on request only between VFR and IFR)	SERVICES Flight information service	SERVICES
					VMC MINIMA	
		8 km FL 100 5 km 1500 m 1500 m 1500 m 1500 m	8 km FL 100 5 km 1000 ft 1500 m 1500 m	8 km FL 100 5 km 1500 m 1500 m 1500 m 1500 m	8 km FL 100 5 km	8 km FL 100 5 km
	VFR				1000 ft 	The higher of: 3000 ft or AMSL or 5 km
					<u></u>	
		SPEED Not applicable	SPEED LIMITATION (2) below FL 100	SPEED LIMITATION (2)	SPEED LIMITATION (2) below FL 100	SPEED LIMITATION (2)
		RADIO	RADIO	RADIO	RADIO Not required (8) (3)	(2) RADIO (3)
		TRANSPONDER A,C	TRANSPONDER A,C	TRANSPONDER A,C	TRANSPONDER A,C	TRANSPONE
		CLEARANCE EATO	CLEARANCE	CLEARANCE	CLEARANCE Not required (7)	CLEARANCE
		adopted but not implemented				

(1) Adopted but not implemented

(2) Not applicable to military aircraft

(3) Before crossing international FIR boundaries a position

report is required for aircraft entering Italian airspace

(4) VMC minima are provided for guidance to pilots with regard to contingency situations which include reference to VMC (Communication failure)

(5) Lower flight visibility to 1500 M is permitted for flights operating at speeds of 140 KTS or less.

Helicopters may operate in less than 1500 M flight visibility, if manoeuvred at a speed which gives, having regard to visibility, adequate opportunity to observe other traffic or any obstacles in time to avoid collision.

(6) Applicable to airplanes and helicopters only(7) Unless otherwise specified in RAC 4(8) Unless otherwise specified in ENR 2.1.1 and RAC 4

